

### WARNING:

#### Please read before installation!

This rim has been designed to meet international TLR (tubeless ready) standards, however, suitable rim tape needs to be applied to the rim after wheel building in order to complete the tubeless ready condition. Check with a dealer specialist to acquire suitable TLR rim tape.

When you ride beyond your limits, cycling can be dangerous. Take a good look at the trails before you shred them, and don't follow an idiot. You should read our instructions carefully before assembly. **FAILURE TO FOLLOW** these instructions before installing and using Ambit components can result in long, boring, unintentional bike-riding breaks, as well as serious injury or death.

**ARTICLE #** AC23 005 RIM

**RIDE INTENTION:** CATEGORY 5 / ENDURO & DH


**USAGE:** FRONT SPECIFIC, REAR SPECIFIC (29" ONLY)

**DIAMETERS AVAILABLE:** 26, 27.5, 29"

### PACKAGE CONTENTS

Rim

**IMPORTANT:** Ambit flat spoke nipple washers are required for assembly but are not included. When building wheels, only use Ambit flat washers. Do not use concave washers.



### WARRANTY

All Ambit parts are warranted for two years from the date of purchase against material defects and manufacturer workmanship. Warranty claims will require an original invoice and will be handled by a dealer specialist or Sport Import. The warranty does not apply to damage caused by riding outside of normal conditions and/or by misuse or failure to follow these instructions for use. Your statutory rights are not affected by this warranty.

**DRILLINGS AVAILABLE:** 28H OR 32H

**FINISH:** BLACK ANODIZED

**TIRE COMPATIBILITY:** TUBELESS READY (TLR)

### TOOLS REQUIRED FOR WHEEL BUILDING:

- Wheel truing stand.
- Spoke nipple tool (size dependent on final nipple selection).
- Wheel dish checking tool.
- Spoke Tension Meter

### TECHNICAL DATA

**Material:**

AL6069 T6

**Rim Depth:**

Front: 18.5mm

Rear: 21.0mm

**Rim Outer Width:**

Front: 36.6mm

Rear: 37.6mm

**Effective Rim Diameter (ERD):**

26" Outer/Inner: 559/530mm

27.5" Outer/Inner: 584/565mm

29" Outer/Inner: 559/530mm

**Weights:**

26" Front & Rear: 627g

27.5 Front & Rear: 644g


29" Front: 639g

29" Rear: 684g

**Spokes & Nipples:**

Rim drilling compatible with 14G or 15G spokes & nipples.

Brass material nipples are recommended for overall strength and longevity.



### MAINTENANCE + TIPS

Before each ride, carefully check the wheel for trueness, spoke tension and for signs of damage. If service is required, you may need to visit a specialist dealer or send the component to Sport Import Service, Industriestrasse 39, 26188 Edewecht, Germany.